



Main

Commercial Status	Commercialised
Aesthetic name	Unica (standard aesthetic)
Product or component type	1 socket-outlet with hinged flap
Device presentation	Mechanism
Outlet poles configuration	2P + E with shutters
Outlet standard	German
Outlet standard description	Side earth
Rated current	16 A, 250 V AC, 50/60 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Cover plate colour tint	White

Complementary

Connections - terminals	Screw terminals
Cable cross section	<= 4 mm ² (rigid) <= 4 mm ² (flexible)
Minimum load breaking capacity	100 operations 1.25 I _n and 1.1 U _n , cos phi: 0.6
Electrical durability	10000 cycles (cos phi: 0.8)
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	> 2000 V
Material	Mechanism cover: ASA + PC
Quantity per set	Blister: set of 1
Standards	IEC 60884-1 VDE 0620-1 UNE 20315-1-2 BS 1363-1 BS 546:1950 NFC 61-314 NOM-003-SCFI-2000 SI 32
Product certifications	14.10.01/5433 FR.ME63.B02375 AC
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
Embedding depth	30 mm
Depth	40 mm
Width	45 mm
Height	45 mm
Product weight	0.0408 kg

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0622 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Period	18 months
--------	-----------